



DATA SHEET

2009-07-17

Page 1 / 3

DAB PUMPS S. p. A.
Via Marco Polo, 14 - 35035 Mestrino (PD) - Italy
Ph. +39 049 9048811 - Fax +39 049 9048847
Http://www.dabpumps.com

Receiver

Society
Reference
Address
Telephone
Fax
E-mail

From

MARCO PUMPS
Louvros, John
97, Athens-Piraeus Ave.
+30 210 4830329
+30 210 4833358
sales@marcopumps.gr

Item no. 1D4311BE2

Pump data :

Model :
NKP-G 65-200/200/A/BAQE/22/2
Impeller size 200 mm
Pressure rating : PN 16
Min. fluid temperature : -10 °C
Max. fluid temperature : 140 °C
Max. Temperature operating : 40 °C

Requested data :




Flow 0,00 m³/h
Head 0,00 m
Fluid : Water, pure
Fluid Temperature : 20 °C
Density : 0,9983 kg/dm³
Kinematic viscosity 1,005 mm²/s
Vapor pressure : 2,34 kPa

Hydraulic data (duty point)

Flow
Head
NPSH :
Shaft power P2 :
Efficiency :

Materials :

Pump body Cast iron 250 UNI ISO 185
Support Cast iron 250 UNI ISO 185
Impeller Cast iron 250 UNI ISO 185
Mechanical seal Carbon/Silicon carbide - EPDM
OR ring Etyilene propylene (EPDM)
Pump shaft AISI 304 X5 Cr Ni 1810 UNI 6900/71
Motor AISI 304 X5 Cr Ni 1810 UNI 6900/71



Weight : 188,1 kg

Motor data :

Trade mark : EURONORM
Nominal power P2 : 22 kW
Rated speed: 2930 1/min
Rated voltage : 3~ 400 V 50 Hz
Nominal current : 39,5 A
Degree of protection : IP 55

Dimension

mm

*	-	M1	-
8	8	M2	-
A	100	N1	320
B	55	N2	279
DNA	80	S1	M 12
DNM	65	W	385
E	241	X	100
F	602		
G	350		
H1	180		
H2	225		
L	343		

Pump connection

Suction side DN 80 / PN 16
Discharge side DN 65 / PN 16